

Frequently Asked Questions

Question

```
mount_smbfs 8 ; 8 < > = B 8 @ > 2 0 = 8 5 2 8 = 4 > 2 K E H 0 @ = 0 FreeBSD
```

Answer

```
2 5 @ A 8 8 FreeBSD 5* < > = B 8 @ > 2 0 = 8 5 ? @ > 8 7 2 > 4 8 ; > A L ? @ 8 ? > <> 1 8  
2 > B B 0 : > 3 > 2 > B = 0 1 > @ 0:
```

```
mount -t smbfs -o username=linuxuser,password=apache  
//fileserver/sysserv /mnt
```

```
@ 8 G 5 < A 8 A B 5 < 0 A < 1 D A ? > O 2 ; O ; O A L B > ; L : > ? > A ; 5  
C A B 0 => 2 : 8 A 0 < 1 K ( : 0 6 5 B A O , = > <> 3 C 8 > H 8 1 0 B L A O , 4 0 2 =>  
1 K ; > ).  
" 5 ? 5 @ L , 2 FreeBSD > 6 , 5 A B L 2 A B @ > 5 == 0 O : > < 0 = 4 0 , 2 K 3 ; O 4 O 1 0 O 2 > B  
B 0 ::
```

```
/usr/sbin/mount_smbfs -I 192.168.1.6 -N //user@Backup/backup /mnt/backup
```

```
4 5 - N - C A ; > 2 8 5 1 @ 0 B L ? 0 @ > ; L 8 7 : > = D 8 3 D 0 9 ; 0 , ; 5 6 0 1 5 3 > 2 /etc  
8 7 > 2 C 1 5 3 > A O nsmb.conf . ! > 4 5 @ 6 8 < > 5 M B > 3 > D 0 9 ; 0 4 ; O 4 0 == > 3 >  
? @ 8 < 5 @ 0 2 K 3 ; O 4 8 B 2 > B B 0 ::
```

```
[default]  
workgroup=WORKGROUP
```

```
[BACKUP]  
addr=192.168.1.6 # = 5 > 1 O 7 0 B 5 ; L = > ? @ 8  
C : 0 7 0 = 8 8 I  
#  
[BACKUP:USER]  
# use persistent password cache for user 'joe'  
password=superpassword
```

```
1 @ 0 B 8 B 5 2 = 8 < 0 = 8 5 = 0 B > G B > 2 A 5 ? 8 H 5 B A O 7 0 3 ; 0 2 = K < 8  
1 C : 2 0 < 8 . C ... 2 8 = 4 0 E , : A B 0 B 8 , 2 A 5 B 0 : 8 5 A B L ...
```

Vampyr`s House!

<https://www.415.spb.ru/ins/faq/faq.php?0.cat.13>

! B @ 0 = 8 F 0 2/2

Details

Info Sunday 14 March 2010 - 18:21:30 by

Vampyr`s House!