

Frequently Asked Questions

Question

= A B @ C < 5 = B ? > 4 > 1 = K 9 tcpdump = 0 Cisco

Answer

2 B > @: Misha Volodko

1. Cisco PIX/ASA

```
ciscoasa(config)#access-list inside_test permit icmp any host
192.168.1.1
```

```
ciscoasa(config)#capture inside_interface access-list inside_test
interface inside
```

The user pings the inside interface of the ASA (ping 192.168.1.1). This output is displayed.

```
ciscoasa#show capture inside_interface
```

```
1: 13:04:06.284897 192.168.1.50 > 192.168.1.1: icmp: echo request
```

2. Cisco router

```
!>7405< ip access-list :>B>@K<1C45<">28BL"8=B5@5ACNI89=0A
B@0D8:.
```

```
routerA(conf)# access-list 111 permit ip 10.10.10.0 0.0.0.255
10.10.15.0 0.0.0.255
```

```
routerA(conf)# access-list 111 permit ip 10.10.15.0 0.0.0.255
10.10.10.0 0.0.0.255
```

```
0?CA:05<:><0=4C=02K?>;=5=858A<>B@8<@57C;LB0B:
```

```
routerA# debug ip packet 111 detail
```

```
IP packet debugging is on (detailed) for access list 111
```

```
Mar 1 00:10:32.975: IP: tableid=0, s=10.10.10.5 (FastEthernet0/0),
d=10.10.15.1 (Serial2/0), routed via FIB
```

-B>@5H5=85=5@01>B05B A fast-switching (ip route-cache).

Vampyr`s House!

<https://www.415.spb.ru/ins/faq/faq.php?0.cat.18>

! B @ 0 = 8 F 0 2/2

Details

Info Sunday 14 March 2010 - 18:46:46 by

Vampyr`s House!